

## **Ameri-Drain®**

As one of the more popular metal panels for the post-frame market, the 29-gauge Ameri-Drain® panel provides a traditional aesthetic and the durability necessary for your building project.

## **Product Specifications**

Applications: Roof and Wall Coverage Widths: 36" Rib Spacing: 6" Rib Height: ½"

Panel Attachment: Exposed Fastening Metal Panel

Gauges: 29, 26

Finishes: Siliconized Polyester


Coatings: Galvalume Plus®, Signature® 200

## Features and Benefits

Class A UL Fire Rating is available

Class 4 UL Impact Rating





CATEGORY	CHARACTERISTIC	TEST METHOD	PURPOSE	RESULT
ENVIRONMENTAL	Impact Resistance	UL 2218	Determines Impact Resistance of prepared Roof Covering Materials	Class 4 Rating
FIRE RESISTANCE	Room Fire Performance	UL 790	Standard for Standard Test Methods for Fire Tests of Roof Coverings	See Class A Fire Rating Data Sheet
STRUCTURAL	Negative Wind Loads	AISI S100	North American Specification for the Design of Cold-Formed Steel Structural Members	See Section Properties and Allowable Load Table Section
	Gravity Loads	AISI S100	North American Specification for the Design of Cold-Formed Steel Structural Members	See Section Properties and Allowable Load Table Section



For a complete line of trim and accessories, please refer to our Trim and Accessories catalog.

ABCMETAL.com

Adel, GA Ennis, TX Lubbock, TX Memphis, TN Nicholasville, KY Omaha, NE Oskaloosa, IA Phoenix, AZ Rome, NY Salt Lake City, UT 800.345.0044 800.481.3035 800.877.8709 800.877.8709 800.345.0044 800.345.0044 800.481.3035 800.544.2651 800.481.3035 800.877.8709